

EC426

Meets / Exceeds EN856 4SP



# Part No.	DN	Hose I.D.		Hose O.D.		Max Operating Pressure		Burst Pressure		Minimum Bend Radius		Weight	
		mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
EC426-06	10	9,5	0.38	22,2	0.87	445	6450	1780	25800	180	7.09	0,73	0.49
EC426-08	12	12,7	0.50	25,4	1.00	415	6000	1660	24000	230	9.06	0,88	0.59
EC426-10	16	15,9	0.62	29,0	1.14	350	5100	1400	20400	250	9.84	1,04	0.70
EC426-12	19	19,0	0.75	33,0	1.30	350	5100	1400	20400	300	11.81	1,47	0.99
EC426-16	25	25,4	1.00	40,9	1.61	280	4050	1120	16200	340	13.39	1,90	1.28
EC426-20	31	31.8	1.25	52,4	2.06	210	3050	840	12200	460	18.11	2,93	1.97

Construction

- Synthetic Rubber Tube
- 4 Spiral Wire Reinforcement
- Black Synthetic Rubber Cover
- Ink Transfer Layline

Operating Temperature

-40°C to +100°C
(-40°F to +212°F)

Agency Listings:

MSHA Approved

Application

- High Pressure Hydraulic System
- Petroleum & Water-Based Fluids
- Construction Equipment
- Agriculture Equipment



Powering Business Worldwide