

EC512

Meets / Exceeds EN856 4SH



# Part No.	DN	Hose I.D.		Hose O.D.		Max Operating Pressure		Burst Pressure		Minimum Bend Radius		Weight	
		mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
EC512-12	19	19,0	0.75	33,0	1.30	420	6100	1680	24400	280	11.02	1,47	0.99
EC512-16	25	25,4	1.00	40,9	1.61	380	5500	1520	22000	340	13.39	2,04	1.37
EC512-20	31	31,8	1.25	52,4	2.06	350	5100	1400	20400	460	18.11	2,39	1.61
EC512-24	38	38,1	1.50	55,1	2.16	290	4200	1160	16800	560	22.05	3,19	2.14
EC512-32	51	50,8	2.00	69,7	2.74	250	3650	1000	14600	700	27.56	4,37	2.94

Construction

- Synthetic Rubber Tube
- 4 Spiral Wire Reinforcement
- Black Synthetic Rubber Cover
- Ink Transfer Layline

Operating Temperature

-40°C to +100°C
(-40°F to +212°F)

Agency Listings:

MSHA Approved

Application

- High Pressure Hydraulic System
- Petroleum & Water-Based Fluids
- Construction Equipment
- Agriculture Equipment

EATON

Powering Business Worldwide